Flexible Windowing for Correlation-Aware Ranking in Anomalous Environments

Anwesha Das[1,2]   Henry Hoffmann[1]   Alex Aiken[2]

[1]The University of Chicago, IL   [2]SLAC National Accelerator Laboratory/Stanford University

**IEEE International Conference on Data Mining (ICDM)**

12 – 15th November 2025

Time-Series Correlations for Anomaly Detection

➜ Incident diagnosis and anomaly detection in systems and facilities
  – Multivariate time-series data monitored from diverse sources
  – Pairwise signal correlations often used to rank signals (e.g., fault localization)
  – Time-windows of signals analyzed as opposed to full signals


➢ What kind of task? Accurate anomaly-relevant signal ranking
  – Bivariate function leading to correlation scores
  – Multivariate associations can be derived from bivariate relations
  – Score-based ranking (assess only top-k signals)

How to select windows from signals for accurate anomaly-relevant ranking?

Window Selection in Anomalous Environments

➜ Prevalent window selection methods
- Fixed size, sliding window with a step size, multiple arbitrary sizes
- Suitable when ((a) in Figure)
  - Adequate/precise failure ground truth (label) is available
  - Same/similar sampling rates, mostly regular (no missing data)
- Inadequate (inaccurate results) when ((b) in Figure)
  - Failure ground truth ⟶ Unavailable or coarse-grained
  - Mixed sampling rates, lots of irregularities
  - Asynchronous data from heterogenous sources

$t \rightarrow timestep$ $m \rightarrow missing\ value$ $w \rightarrow window$

X | t_1 | t_2 | m | | | | | | t_n **X** | t_1 | t_2 | m | | | | | | t_n

Even for regular signals there can be lags in temporal variation !!

Y | t_1 | t_2 | | | | | m | m | t_n **Y** | t_1 | t_2 | | | | | m | m | t_n

(a) Fixed   (b) Flexible

How to select windows from pairwise signals in presence of asynchrony, irregularity, and mixed sampling rates?

Window Selection in Anomalous Environments

➔ Select windows with available coarse-labels
  – Such that bivariate scores are better aligned with anomalous times

Fixed Windows
(same positions, i.e., start/end times)

Flexible Windows
(different positions)

Fixed-windows: Time-localized deviations may not be well aligned with anomalies if same start and end times of windows are considered across diverse signals !!

Our Method: AdaptWin

➔ Leverage anomaly-indicative symptoms (dips/spikes, graduate/abrupt changes)
  – Inter-arrival times (δ^V), Value-differences (δ^T)
  – *Key idea: Adapt the window position and size based on filtered* δ^V and/or δ^T
  – Filter? Configurable threshold based on distribution of $\delta^V s$ and $\delta^T s$
  – Minimum window size selection (W_{min}): Lower bound
  – Goal: Better accuracy in ranking quality (offline process)

Regular (Same sampling rate)   Regular (Mixed sampling rate)   Irregular (Same sampling rate)   Irregular (Mixed sampling rate)

➔ Non-goals
  – No new ranking method
  – Efficiency: Fast window selection with scale
  – No real-time requirements

AdaptWin

➜ Window Selection
- Specific signal-pairs given for known failure ground truth (context-relevant/manual)
- Select *minimum* and then *actual* windows
- Obtain pairwise scores with correlation functions (e.g., correlation coefficients)

➜ Correlation Analysis
- Analyze ranks with selected windows
- Ground truth validation (top K)
- Comparative analysis (e.g., fixed etc.)

AdaptWin

➜ Set of signal-pairs $[S_i, S_j]$, Correlation Function F, Original window size: W_{max}
 ➜ $[\lambda, \delta^{T]}$ (λ: frequency of distinct δ^T)
  ➜ Identify sampling interval (SI) (mode: most frequent δ^T)

➜ Minimum Window Selection
  – Regular signal (δ^T do not vary): t_{span} = A fraction of W_{max} ($1/g$)
  – Irregular signal:
    – Sort and filter δ^T s
    – Temporal gaps: $t_{span} = \Sigma\ (\delta^T * \lambda)$ for filtered δ^T s
    – $Pair_{min}$ = max of (t_{span} s), W_{min} = max of ($Pair_{min}$ s)

Intuition: Long enough to capture major patches of unevenness in the window !!

AdaptWin

- ➢ Actual Window Selection
    - ➜ Unique observational differences: [Frequency α, δ^V]
    - ➜ Sort and filter δ^V s
    - ➜ *Prioritize* time-steps with changes in both δ^V and δ^T > those with δ^V only > those with δ^T only: [(δ^V, δ^T) > δ^V > δ^T]
    - ➜ Prioritizing *reduces number of candidate windows* (not all possible start time-steps)
        - ➜ Shortlisted Location Indices [L_k]: *Lower iterations*

    - ➜ For each *signal-pair*: Common SI (max or min of SI-pair)
        - ➜ Candidate windows W with start times in [L_k] with size W_{min}
        - ➜ Resample with common SI
        - ➜ Extend W by fixed time-steps (β) while optimizing *F*
        - ➜ Obtain actual size: W_{act} with specific window positions

Irregular or Regular Signal   Candidate Windows   Bivariate Correlation

Evaluation

➢ Datasets: Three domains: High-Energy Physics[1] (Particle Accelerator; PAS), Space Weather (SWAN), Train Air Compressor (APU)

➢ Baselines: Fixed, Adwin (univariate); Domain-specific (multivariate): Optwin, Flexwin

➢ Evaluation Metrics for top-K Ranking: Precision@K (P), Recall@K (R), Normalized Discounted Cumulative Gain (NDCG@K)

➢ Functions: Pearson/Spearman Correlation (PC/SC), Dynamic Time Warping (DTW)

Dataset	Signals	Size	Sampling Rate (Hz)	Missing values?	# Failure Instances	Fault Type
PAS	5511	300K	[0.1 – 120]	Yes	14	Water Cooler, Magnet, Pump Trips
SWAN	51	20K	0.08	Yes	11	Solar Flares
APU	15	500K	0.04	No	10	Air/Oil Leaks

➢ Ground truth example: "Water cooler Z failed for $\approx$ 30mins between 10:00 and 18:00 hrs", Unavailable: Signals X and Y of Z was anomalous between 11:00 and 11:30 hrs, Failure Duration: 6-mins to 2-hours

[1]Linac Coherence Light Source (LCLS/SLAC)

Results

➜ W_{max} = 3-hour, Top-15 signals, AdaptWin obtains better ranking quality (**RQ1**)

Method	Pearson's Correlation (PC)									Spearman's Correlation (SC)									Dynamic Time Warping (DTW)								
	PAS			APU			SWAN			PAS			APU			SWAN			PAS			APU			SWAN		
	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG	P	RC	NDCG
Fix	0.06	0.25	0.2	0.16	0.25	0.3	0.06	0.33	0.3	0.06	0.25	0.3	0.1	0.2	0.2	0.06	0.25	0.3	0.19	0.18	0.3	0.12	0.3	0.3	0.2	0.16	0.47
Adwin	0.13	0.05	0.2	0.06	0.05	0.3	0.06	0.2	0.4	0.06	0.25	0.4	0.01	0.01	0.3	0.06	0.25	0.4	0.23	0.33	0.4	0.16	0.25	0.5	0.26	0.25	0.4
Optwin	0.06	0.07	0.1	0.02	0.02	0.12	0.16	0.33	0.1	0.13	0.33	0.4	0.06	0.16	0.12	0.13	0.16	0.35	0.12	0.32	0.14	0.15	0.26	0.21	0.2	0.3	0.3
Flexwin	0.04	0.06	0.1	0.02	0.3	0.45	0.18	0.25	0.5	0.2	0.4	0.3	0.3	0.4	0.3	0.18	0.34	0.4	0.05	0.14	0.21	0.03	0.21	0.19	0.24	0.3	0.31
AdaptWin	**0.3**	**0.56**	**0.5**	**0.22**	**0.5**	**0.6**	**0.25**	**0.66**	**0.6**	**0.8**	**0.76**	**0.67**	**0.4**	**0.6**	**0.4**	**0.2**	**0.4**	**0.5**	**0.35**	**0.53**	**0.5**	**0.4**	**0.5**	**0.7**	**0.4**	**0.56**	**0.6**

➜ Variation of W_{max} and bivariate function (**RQ2**):
  ➜ NDCG@15: Performance is similar for certain other windowing methods
  ➜ Position of relevant signals better with AdaptWin

Method	PAS (SC)				SWAN (SC)				PAS (2.5-hr)		
	2-hr	4-hr	5-hr	6-hr	2-hr	4-hr	5-hr	6-hr	PC	SC	DTW
Fix	0.4	0.2	0.3	0.1	0.3	0.3	0.2	0.2	0.38	0.4	0.4
Adwin	0.2	0.12	0.12	0.1	0.2	0.1	0.02	0.01	0.25	0.2	0.1
Optwin	0.2	0.1	0.1	0.07	0.22	0.19	0.15	0.15	0.1	0.14	0.2
Flexwin	0.3	0.1	0.1	0.07	0.35	0.2	0.21	0.1	0.35	0.3	0.26
AdaptWin	**0.6**	**0.5**	**0.5**	**0.45**	**0.7**	**0.55**	**0.51**	**0.48**	**0.52**	**0.6**	**0.6**

AdaptWin is relatively more accurate overall !

Results

➔ Scalability: With increasing signals, the ranking quality is much better than Fix (**RQ3**)

Scalability

Efficiency

➔ Efficiency: With increasing signals, runtime increases from 0.8 to 4.6 mins for AdaptWin, which is lower than other multivariate methods (**RQ4**)

The runtime considering better ranking quality is worthwhile for AdaptWin !

Results

➔ Time Complexity: *p* signal-pairs with *c* entries each
  – Fixed Size: O(p)
  – Sliding Windows: $O(pc^2)$
  – Brute-force: $O(pc^2m)$, *m* unique window sizes
  – AdaptWin: O(p(c+mn)), *m* and *n* are number of location indices of a pair,
    [m << c, n << c]

➔ Case Study: Boosts ranks of anomaly-indicative signal(s) for a faulty water cooler

Signal	Fix	Adwin	Optwin	Flexwin	Adaptwin
Energy	3	36	41	47	21
Magnet	17	42	37	23	52
Water1	33	37	49	56	**12**
Water2	35	29	44	40	**18**
Water3	49	47	31	61	**10**

Conclusion

➢ Adaptive window selection from a signal-pair
  ➢ 3x better anomaly-relevant ranking
  ➢ Suitable? Asymmetry, Aperiodicity, High dimensional space, Sparse labels
  ➢ Accuracy vs. runtime trade-off worthwhile with scale

➢ Future Work
  ➢ Optimization with pairwise evaluations
  ➢ Other tasks beyond ranking, e.g., regression problems
  ➢ Better bounds based on the nuances of anomalies

AdaptWin selects windows for correlations that improve anomaly-relevant ranking !

Thank You

Backup Slides

Related Work

➔ Univariate methods
  - ➔ Concept drift estimation, Change point detection, Imputation
  - ➔ Time-series segmentation, duplicate detection
  - ➔ Not adequate for bivariate relations

➔ Multivariate methods
  - ➔ Human activity recognition, Localization in seismograms
  - ➔ Feature aggregation, Lagged Correlations, Trend Analysis
  - ➔ Domain-specific or do not consider anomalous environments

➔ Some of the univariate and multivariate methods do not consider *irregularities* or *mixed* sampling rates